


# MPM (Divider)

Vishay Thin Film




## Molded, SOT-23 Resistor Network



Vishay Thin Film MPM Series Dividers provide  $\pm 2$  ppm/ $^{\circ}$ C tracking and a ratio tolerance as tight as 0.01 %, small size, and exceptional stability for all surface mount applications. The standard SOT-23 package format with unity and common standard resistance divider ratios provide easy selection for most applications requiring matched pair resistor elements. The ratios listed are available for off the shelf delivery. If you require a non-standard ratio, consult the applications engineering group as we may be able to meet your requirements with a custom design.

### SCHEMATIC



### FEATURES

- Lead (Pb)-free available
- Stocked
- Standard Footprint



RoHS\*  
COMPLIANT

### TYPICAL PERFORMANCE

	ABS	TRACKING
TCR	25	2
	ABS	RATIO
TOL	0.1	0.05

### STANDARD DIVIDER RATIO (R<sub>2</sub>/R<sub>1</sub>)


RATIO	R <sub>2</sub> (Ω)	R <sub>1</sub> (Ω)
100:1	100K	1K
50:1	50K	1K
25:1	25K	1K
20:1	20K	1K
10:1	10K	1K
9:1	9K	1K
6:1	6K	1K
5:1	10K	2K
5:1	5K	1K
4:1	8K	2K
4:1	4K	1K
2:1	10K	5K
2:1	2K	1K
1:1	50K	50K
1:1	25K	25K
1:1	10K	10K
1:1	5K	5K
1:1	2.5K	2.5K
1:1	1K	1K
1:1	500	500
1:1	250	250

STANDARD ELECTRICAL SPECIFICATIONS		
TEST	SPECIFICATIONS	CONDITIONS
Material	Passivated Nichrome	
TCR:	Tracking	$\pm 2$ ppm/ $^{\circ}$ C (typical)
	Absolute	$\pm 25$ ppm/ $^{\circ}$ C
Tolerance:	Ratio	$\pm 0.5$ % to 0.01 %
	Absolute	$\pm 1.0$ % to $\pm 0.05$ %
Power Rating:	Resistor	100 mW
	Package	200 mW
Stability:	$\Delta R$ Absolute	0.10 %
	$\Delta R$ Ratio	0.03 %
Voltage Coefficient	0.1 ppm/V	
Working Voltage 100 Volts Max.	-	
Operating Temperature Range	- 55 $^{\circ}$ C to + 125 $^{\circ}$ C	
Storage Temperature Range	- 55 $^{\circ}$ C to + 125 $^{\circ}$ C	
Noise	< - 30 dB	
Thermal EMF	0.2 $\mu$ V/ $^{\circ}$ C	
Shelf Life Stability (Ratio)	50 ppm Max.	1 year at + 25 $^{\circ}$ C

\* Pb containing terminations are not RoHS compliant, exemptions may apply




**DIMENSIONS AND IMPRINTING** in inches and millimeters



DIMENSION	INCHES		MM	
	MIN.	MAX.	MIN.	MAX.
A	0.031	0.040	0.79	1.02
A1	0.001	0.004	0.02	0.10
B	0.105	0.120	2.67	3.05
S	0.071	0.079	1.80	2.00
W	0.015	0.021	0.38	0.54
L	0.083	0.098	2.10	2.50
H	0.047	0.055	1.20	1.40
T	0.005	0.010	0.13	0.25
J	0.0035	0.0059	0.089	0.15
K	0.017	0.022	0.44	0.55
Ø	0	8°	0	8°

MECHANICAL SPECIFICATIONS	
Resistive Element	Passivated Nichrome
Substrate Material	Silicon
Body	Molded epoxy
Terminals	Copper alloy #42 Sn62 plated
Lead Coplanarity	3 Mils Max.
Lead (Pb)-free Option	100 % Sn Matte
Lead (Pb)-free Finish	Plated

**DERATING CURVE**



**GLOBAL PART NUMBER INFORMATION**

New Global Part Numbering: **MPM1002AWS** (preferred part number format)

M	P	M	1	0	0	3	A	W	S					
M	P	M	T	1	0	0	1	5	0	0	1	A	T	1

GLOBAL MODEL (3 or 4 digits)	RESISTANCE (4 or 8 digits)	TOLERANCE AND RATIO TOLERANCE	PACKAGING
<b>MPM</b> (Tin Lead)  <b>MPMT</b> (Lead (Pb)-free) (e3)	First 3 digits are significant figures and the last digit specifies the number of zeroes to follow. When like values are required use total resistance. When dual values are required list both values.  Example: (list R1 first in part number with dual values) 1002 = 10K (5K/5K) 1003 = 100K (50K/50K) 10011002 = 1K/10K divider	Abs. Tol.      Ratio <b>A</b> = 0.1 %      0.05 % <b>B</b> = 0.1 %      0.1 % <b>C</b> = 0.25 %    0.1 % <b>D</b> = 0.5 %      0.1 % <b>F</b> = 1 %        0.5 % <b>*Z</b> = 0.1 %    0.025 % <b>*Q</b> = 0.05 %   0.01 %  * Tol. Available 1K and up equal values only	<b>BS</b> = BULK 100 Min 1 Mult <b>WS</b> = WAFFLE 100 Min 1 Mult  TAPE AND REEL <b>T0</b> = 100 Min 100 Mult <b>T1</b> = 1000 Min 1000 Mult <b>T3</b> = 300 Min 300 Mult <b>T5</b> = 500 Min 500 Mult <b>TF</b> = Full Reel 4000 <b>TS</b> = 100 Min 1 Mult

Historical Part Number example: **MPM1002BW** (will continue to be accepted)

MPM	1002	B	W
SERIES	RESISTANCE	TOLERANCE AND RATIO TOLERANCE	PACKAGING



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.