

SANYO	No.2006A	2SA1417/2SC3647
	PNP/NPN Epitaxial Planar Silicon Transistors High-Voltage Switching Applications	

Features

- . Adoption of FBET, MBIT processes.
- . High breakdown voltage and large current capacity.
- . Fast switching time.
- . Very small size making it easy to provide high-density, small-sized hybrid ICs.

(): 2SA1417

Absolute Maximum Ratings at Ta=25°C		unit
Collector to Base Voltage	V_{CB0}	(-)120 V
Collector to Emitter Voltage	V_{CEO}	(-)100 V
Emitter to Base Voltage	V_{EBO}	(-)6 V
Collector Current	I_C	(-)2 A
Collector Current(Pulse)	I_{CP}	(-)3 A
Collector Dissipation	P_C	500 mW
	Mounted on ceramic board (250mm ² x 0.8mm)	1.5 W
Junction Temperature	T_j	150 °C
Storage Temperature	T_{stg}	-55 to +150 °C

Electrical Characteristics at Ta=25°C		min	typ	max	unit
Collector Cutoff Current	I_{CBO} $V_{CB}=(-)100V, I_E=0$			(-)100	nA
Emitter Cutoff Current	I_{EBO} $V_{EB}=(-)4V, I_C=0$			(-)100	nA
DC Current Gain	h_{FE} $V_{CE}=(-)5V, I_C=(-)100mA$	100*		400*	
Gain-Bandwidth Product	f_T $V_{CE}=(-)10V, I_C=(-)100mA$		120		MHz
Output Capacitance	c_{ob} $V_{CB}=(-)10V, f=1MHz$		(25)		pF
			16		pF
C-E Saturation Voltage	$V_{CE(sat)}$ $I_C=(-)1A, I_B=(-)100mA$		(-)0.22	(-)0.6	V
			0.13	0.4	V
B-E Saturation Voltage	$V_{BE(sat)}$ $I_C=(-)1A, I_B=(-)100mA$		(-)0.85	(-)1.2	V
C-B Breakdown Voltage	$V_{(BR)CBO}$ $I_C=(-)10\mu A, I_E=0$		(-)120		V
C-E Breakdown Voltage	$V_{(BR)CEO}$ $I_C=(-)1mA, R_{BE}=\infty$		(-)100		V
E-B Breakdown Voltage	$V_{(BR)EBO}$ $I_E=(-)10\mu A, I_C=0$		(-)6		V

* The 2SA1417/2SC3647 are classified by 100mA h_{FE} as follows:

100	R	200	140	S	280	200	T	400
-----	---	-----	-----	---	-----	-----	---	-----

Continued on next page.


Marking 2SA1417:AC

2SC3647:CC

h_{FE} rank :R,S,T

Package Dimensions 2038

(unit:mm)



(Bottom View)


SANYO: PCP

SANYO Electric Co., Ltd. Semiconductor Business Headquarters
 TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN







Continued from preceding page.

			min	typ	max	unit
Turn-ON Time	t_{on}	See specified Test Circuit.		(80)		ns
				80		ns
Storage Time	t_{stg}			(750)		ns
				1000		ns
Fall Time	t_f			(40)		ns
				50		ns









Switching Time Test Circuit





Unit (Resistance : Ω , Capacitance : F)
 $10|IB1| = -10|IB2| = I_C = 0.7A$ (For PNP, the polarity is reversed.)



2SA1417/2SC3647





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.